



**AI TECHNOLOGY INC**  
 70 Washington Road  
 Princeton Jct., NJ 08550  
 (609) 799-9388 fax (609) 799-9308  
 E-Mail: ait@aitechnology.com  
 Internet: http://www.aitechnology.com

**COOL-PAD**  
**CP7108**

**Flexible From -55 to 150°C**  
**"Phase-Change" Dry Pad**  
**High Melt-flow >135°C**  
**Bond with Placement Pressure**

**IDEAL FOR:**

- Thermal Grease Replacement**
- Thermal Adhesive Paste Replacement**
- Thermal Gasket Replacement**
- BGA Heatspreader-Die Attachment**

**DESCRIPTION:**

CP7108 is an aluminum nitride crystallite filled, electrically insulating, medium bond strength thermal interface material designed to enhance thermal transfer from power device to heat-sink. CP7108 is dry and handles well with automated excise-placement equipment and forms good bond with placement pressure similar to paste adhesives.

**AVAILABILITY:**

CP7108 is available in sheet sizes, reel, and as custom preforms. Standard thicknesses are 0.003" and 0.006". Special thicknesses are available.

**APPLICATION PROCEDURES:**

- ( 1 ) Cut or pre-cut to desired size and shape.
- ( 2 ) Place COOL-PAD between device and heat-sink.
- ( 3 ) If it is pre-applied onto heatspreader or die, bond parts at >135°C with placement pressure.

**TYPICAL PROPERTIES\***

Electrical Resistivity ( 25°C/ 1s is )	>1X10 <sup>14</sup> ohm-cm
Dielectric Strength (Volts/mil)	>550
Glass Transition Temp.(°C)	-55
Lap-Shear Strength	<600 psi <4.1 N/mm <sup>2</sup>
Device Push-off Strength	<900 psi <6.2N/mm <sup>2</sup>
Hardness (Type)	<60 (A)
Cured Density (gm/cc)	2.5
Thermal Conductivity	>28 Btu-in/hr-ft <sup>2</sup> -°F >4.0 W/m-°C
Linear Thermal Expansion Coeff. (ppm/°C)	110
Maximum Continuous Operation Temp. (°C)	150

\* Properties given are typical values and not intended for use in preparing specifications. The user is advised to evaluate the product in the manner the product is intended to be used in manufacturing and in the final product.

**Melt/Flow Conditions**

<u>Temperature</u>	<u>Time</u>	<u>Pressure</u>
>135°C	0.5 sec	Nominal

**SHELF LIFE:**

<u>Storage temperature</u>	<u>Shelf Life</u>
25°C	1 yr

**CAUTION:** This product may cause skin irritation. Avoid skin contact. If contact does occur, wash immediately with soap and water. Please refer to MSDS for more details.

The information contained herein is believed to be reliable. All recommendations or suggestions are made without guarantee inasmuch as conditions and methods of commercial use are beyond our control. Properties given are typical values and not intended for use in preparing specifications. The user is advised to evaluate the product in the manner the product is to be used in manufacturing and in the final product. Under no circumstance shall A.I. Technology be liable for accidental, consequential or other damages arising from the use or handling of this product.

While AI Technology owns all proprietary rights of material formulations of its products, specific usage in the manufacturing of certain products may involve patent rights of other companies.